

Page 1/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1 Identification

· Product identifier

- 1.1 Trade name: Wieland-U33
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the article: Semi-finished product
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Wieland-Werke AG Graf-Arco-Str. 36 89079 Ulm
- Information department: ESG Affairs stefan.priggemeyer@wieland.com
- 1.4 Telephone number: +49 731 944 2794 (Monday Friday from 9 a.m. to 4 p.m.)

2 Hazard(s) identification

2.1 Classification of the substance or mixture:



GHS08 Health hazard

Carcinogenicity 2

Specific Target Organ Toxicity - Repeated Exposure 1

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

GHS07

H317 May cause an allergic skin reaction.

- Sensitization Skin 1 • 2.2 Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms: GHS07, GHS08
- · Signal word: Danger
- · Hazard statements:
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)



Page 2/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

(Contd. of page 1)

1.1 Trade name: Wieland-U33

P363	Wash contaminated clothing before reuse.
------	--

- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable to metals.
- · vPvB: Not applicable to metals.

3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- **Description:** Metal in massive form.
- · Material Code (CEN/TS 13388): CuAl10Ni5Fe4
- · Material number (CEN/TS 13388): CW307G
- · UNS-number: C63000

· Information:

The classifications listed below reflect the classification of the relevant alloying constituents and are only for information.

Mentioned percentages are references values.

Components:

balance%
9.0-11.0%
4.0-5.5%
2.0-4.0%
max. 1%
max. 0.05%

4 First-aid measures

· 4.1 Description of first aid measures

· General information:

First Aid information refer to any dust which is generated.

The mixture in solid form does not pose any significant health hazard. However, melting or activites which produce metal dust, smoke or fumes can cause that metal dust enter the body in harmful amounts.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

US



Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1.1 Trade name: Wieland-U33

• After eye contact:

(Contd. of page 2)

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

5 Fire-fighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents: Non-flammable. Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures: Not required.
- · 6.2 Environmental precautions: Not required.
- **6.3 Methods and material for containment and cleaning up:** Collect the material and if necessary dispose it as waste according to section 13.
- 6.4 Reference to other sections: See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · 7.1 Precautions for safe handling: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Further information about storage conditions: Store in dry conditions.
- 7.3 Specific end use(s): No further relevant information available.

(Contd. on page 4)



Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1.1 Trade name: Wieland-U33

(Contd. of page 3)

- US -

8 Exposure controls/personal protection	
· Additional information about design of technical systems: No further data; se	e item 7.
 8.1 Control parameters Components with limit values that require monitoring at the workplace: 	
7440-50-8 copper	
PEL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
REL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume	
7429-90-5 Aluminium	
PEL Long-term value: 15*; 5** mg/m³ *Total dust; ** Respirable fraction	
REL Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.	
7440-02-0 nickel	
PEL Long-term value: 1 mg/m³	
REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A	
TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI	
7439-96-5 manganese	
PEL Ceiling limit value: 5 mg/m³ as Mn	
REL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ fume, as Mn	
TLV Long-term value: 0.02* 0.1** mg/m³ as Mn; A4, *respirable **inhalable fraction	
7439-92-1 lead	
PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025	
REL Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C	
TLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3	
	(Contd. on page 5)



Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1.1 Trade name: Wieland-U33

	(Contd. of page 4
Ingredients with biological limit values:	
7440-02-0 nickel	
BEI 5 µg/L	
Medium: urine Time: post-shift at end of workweek	
Parameter: Nickel (background)	
30 µg/L	
Medium: urine	
Time: post-shift at end of workweek Parameter: Nickel (background)	
7439-92-1 lead	
βΕΙ 200 μg/L	
Medium: blood	
Time: not critical	
Parameter: Lead	
Additional information: The lists that we	re valid during the creation were used as basis.
 Protection of hands: Protective gloves are recommended, depergloves: neoprene or leather). Eye protection: Protective goggles are recommended, depergloyed by protection: 	ustrial gas mask when work-place-limits are exceeded. ending upon how the semis are further processed (material o pending upon how the semis are further processed. ng upon how the semis are further processed.
Physical and chemical properties	\$
• 9.1 Information on basic physical and c	hemical properties
Appearance:	
Color:	metallic-yellow
Odor:	Odorless
Odor threshold:	Not determined.
Change in condition	
Melting point/Melting range:	1050-1080 °C (1922-1976 °F)
Boiling point/Boiling range:	Undetermined.



Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1.1 Trade name: Wieland-U33

	(Contd. of page 5)
· Flash point:	Not applicable.
Density at 20 °C (68 °F):	7.5 g/cm ³ (62.5875 lbs/gal)
Solubility in / Miscibility with water at 20 °C (68	
°F):	Not soluble.
· Solvent separation test	
VOC content:	0.00 %
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

· 10.1 Reactivity: Not applicable.

· 10.2 Chemical stability: Not applicable.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions:** No dangerous reactions known.
- 10.4 Conditions to avoid: No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

• Acute toxicity: Based on available data, the classification criteria are not met.

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information: When used and handled according to specifications, the article does not have any harmful effects to our experience and the information provided to us.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

7440-02-0 nickel: 2B 7439-92-1 lead: 2B

· NTP (National Toxicology Program)

7440-02-0 nickel: R 7439-92-1 lead: R

(Contd. on page 7)



(Contd. of page 6)

Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1.1 Trade name: Wieland-U33

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · 12.1 Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability:** No further relevant information available.
- 12.3 Bioaccumulative potential: No further relevant information available.
- **12.4 Mobility in soil:** No further relevant information available.
- · General notes: Semi-finished articles from copper and copper-alloys are not soluble in water.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.
- · 12.6 Other adverse effects: No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation: Contact manufacturer for recycling information.

· 14.1 UN-Number · DOT, ADR, IMDG, IATA	Void	
14.2 UN proper shipping name DOT, ADR, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · DOT, ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user:	Not applicable.	
 14.6 Special precautions for user: 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code: 		

(Contd. on page 8)



Page 8/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

1.1 Trade name: Wieland-U33

(Contd. of page 7)

Regulatory information	
15.1 Safety, health and environmental regulations/legislation specific for the mixture	he substance or
Sara Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
7440-50-8 copper	
7429-90-5 Aluminium	
7440-02-0 nickel	
7439-96-5 manganese	
7439-92-1 lead	
TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants:	
7439-96-5 manganese	
7439-92-1 lead	
Proposition 65 Chemicals known to cause cancer:	
7440-02-0 nickel	
7439-92-1 lead	
Chemicals known to cause reproductive toxicity for females:	
7439-92-1 lead	
Chemicals known to cause reproductive toxicity for males:	
7439-92-1 lead Chemicals known to cause developmental toxicity:	
7439-92-1 lead	
Cancerogenity categories EPA (Environmental Protection Agency):	
7440-50-8 copper: D	
7439-96-5 manganese: D	
7439-92-1 lead: B2	
TLV (Threshold Limit Value established by ACGIH):	
7429-90-5 Aluminium: A4	
7440-02-0 nickel: A5	
7439-92-1 lead: A3	
NIOSH-Ca (National Institute for Occupational Safety and Health):	
7440-02-0 nickel	
	(Contd. on page



Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing date 12/14/2023

Version - No. 1

Reviewed on 12/14/2023

(Contd. of page 8)

1.1 Trade name: Wieland-U33

· Chemical safety assessment: Void.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific article features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: ESG Affairs

Contact:

Dr. Stefan Priggemeyer Phone +49 731 944 2794 Email: stefan.priggemeyer@wieland.com

- US