

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

### 1 Identification

- **Product identifier**
- **1.1 Trade name:** **eco M43**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the article:** Semi-finished product
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Wieland-Werke AG  
Graf-Arco-Str. 36  
89079 Ulm  
Germany
- **Information department:**  
ESG Affairs  
stefan.priggemeyer@wieland.com
- **1.4 Telephone number:** +49 731 944 2794 (Monday - Friday from 9 a.m. to 4 p.m.)

### 2 Hazard(s) identification

- **2.1 Classification of the substance or mixture:**  
The product is not classified, according to the Globally Harmonized System (GHS).
- **2.2 Label elements:**
- **GHS label elements** Void
- **Hazard pictograms:** Void
- **Signal word:** Void
- **Hazard statements:** Void
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable to metals.
- **vPvB:** Not applicable to metals.

### 3 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Metal in massive form.
- **Material Code (CEN/TS 13388):** CuZn38As
- **Material number (CEN/TS 13388):** CW511L
- **UNS-number:** C27453
- **Information:**  
The classifications listed below reflect the classification of the relevant alloying constituents and are only for information.  
Mentioned percentages are references values.
- **Components:**

7440-50-8 copper

61.5-63.5%  
(Contd. on page 2)

US

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

#### 1.1 Trade name: **eco M43**

		(Contd. of page 1)
7440-66-6 zinc		Balance%
7440-02-0 nickel		max. 0.3%
	❖ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 1, H372; ❖ Sensitization - Skin 1, H317	
7439-92-1 lead		max. 0.100%
	❖ Carcinogenicity 2, H351; Toxic to Reproduction 1A, H360; ❖ Aquatic Chronic 1, H410	
7440-38-2 arsenic		0.02-0.15%
	❖ Acute Toxicity - Oral 3, H301; Acute Toxicity - Inhalation 3, H331; ❖ Carcinogenicity 1A, H350; ❖ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

#### 4 First-aid measures

- **4.1 Description of first aid measures**

- **General information:**

First Aid information refer to any dust which is generated.

The mixture in solid form does not pose any significant health hazard. However, melting or activities which produce metal dust, smoke or fumes can cause that metal dust enter the body in harmful amounts.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Rinse out mouth and then drink plenty of water.

- **4.2 Most important symptoms and effects, both acute and delayed:**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

#### 5 Fire-fighting measures

- **5.1 Extinguishing media**

· **Suitable extinguishing agents:** Non-flammable. Use fire fighting measures that suit the environment.

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

- **5.3 Advice for firefighters**

· **Protective equipment:** No special measures required.

US

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

### 1.1 Trade name: **eco M43**

(Contd. of page 2)

### 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures:** Not required.
- **6.2 Environmental precautions:** Not required.
- **6.3 Methods and material for containment and cleaning up:**  
Collect the material and if necessary dispose it as waste according to section 13.
- **6.4 Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **7.1 Precautions for safe handling:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Further information about storage conditions:** Store in dry conditions.
- **7.3 Specific end use(s):** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **8.1 Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

#### **7440-50-8 copper**

PEL Long-term value: 1\* 0.1\*\* mg/m<sup>3</sup>  
as Cu \*dusts and mists \*\*fume

REL Long-term value: 1\* 0.1\*\* mg/m<sup>3</sup>  
as Cu \*dusts and mists \*\*fume

TLV Long-term value: 1\* 0.2\*\* mg/m<sup>3</sup>  
\*dusts and mists; \*\*fume; as Cu

#### **7440-02-0 nickel**

PEL Long-term value: 1 mg/m<sup>3</sup>

REL Long-term value: 0.015 mg/m<sup>3</sup>  
as Ni; See Pocket Guide App. A

TLV Long-term value: 1.5\* mg/m<sup>3</sup>  
elemental, \*inhalable fraction, A5, BEI

(Contd. on page 4)

us

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

#### 1.1 Trade name: **eco M43**

(Contd. of page 3)

##### **7440-38-2 arsenic**

PEL Long-term value: 0.5\* 0.01\*\* mg/m<sup>3</sup>  
as As; \*organic\*\*inorg. compds.; 29 CFR 1910.1018

REL Ceiling limit value: 0.002 mg/m<sup>3</sup>  
as As; 15min; See Pocket Guide App. A

TLV Long-term value: 0.01 mg/m<sup>3</sup>  
as As; BEI, A1

##### **7439-92-1 lead**

PEL Long-term value: 0.05\* mg/m<sup>3</sup>  
\*see 29 CFR 1910.1025

REL Long-term value: 0.05\* mg/m<sup>3</sup>  
\*8-hr TWA ;See PocketGuide App.C

TLV Long-term value: 0.05\* mg/m<sup>3</sup>  
\*and inorganic compds., as Pb; BEI, A3

· **Ingredients with biological limit values:**

##### **7440-02-0 nickel**

BEI 5 µg/L

Medium: urine  
Time: post-shift at end of workweek  
Parameter: Nickel (background)

30 µg/L  
Medium: urine  
Time: post-shift at end of workweek  
Parameter: Nickel (background)

##### **7440-38-2 arsenic**

BEI 35 µg As/L  
Medium: urine  
Time: end of workweek  
Parameter: Inorganic arsenic plus methylated metabolites (background)

##### **7439-92-1 lead**

BEI 200 µg/L  
Medium: blood  
Time: not critical  
Parameter: Lead

· **Additional information:** The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Do not inhale dust / smoke / mist.

· **Breathing equipment:** Use a suitable industrial gas mask when work-place-limits are exceeded.

(Contd. on page 5)

us

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

#### 1.1 Trade name: **eco M43**

(Contd. of page 4)

· **Protection of hands:**

Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather).

· **Eye protection:**

Protective goggles are recommended, depending upon how the semis are further processed.

· **Body protection:**

Wear suitable protective clothing, depending upon how the semis are further processed.

## 9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Color:

Brass yellow

Odor:

Odorless

· **Odor threshold:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

870-903 °C (1598-1657.4 °F) (Lit.)

· **Boiling point/Boiling range:**

Undetermined.

· **Flash point:**

Not applicable.

· **Density at 20 °C (68 °F):**

8.39 g/cm³ (70.01455 lbs/gal) (Lit.)

· **Solubility in / Miscibility with water at 20 °C (68 °F):**

Not soluble.

· **Solvent separation test**

**VOC content:**

0.00 %

· **9.2 Other information**

No further relevant information available.

## 10 Stability and reactivity

· **10.1 Reactivity:** Not applicable.

· **10.2 Chemical stability:** Not applicable.

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions:** No dangerous reactions known.

· **10.4 Conditions to avoid:** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

us

(Contd. on page 6)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

**1.1 Trade name: eco M43**

(Contd. of page 5)

**11 Toxicological information**

- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
When used and handled according to specifications, the article does not have any harmful effects to our experience and the information provided to us.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**  
7440-02-0 nickel: 2B  
7440-38-2 arsenic: 1  
7439-92-1 lead: 2B
- **NTP (National Toxicology Program)**  
7440-02-0 nickel: R  
7440-38-2 arsenic: K  
7439-92-1 lead: R
- **OSHA-Ca (Occupational Safety & Health Administration)**  
7440-38-2 arsenic

**12 Ecological information**

- **12.1 Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability:** No further relevant information available.
- **12.3 Bioaccumulative potential:** No further relevant information available.
- **12.4 Mobility in soil:** No further relevant information available.
- **General notes:** Semi-finished articles from copper and copper-alloys are not soluble in water.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable to metals.
- **vPvB:** Not applicable to metals.
- **12.6 Other adverse effects:** No further relevant information available.

US  
(Contd. on page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

### 1.1 Trade name: **eco M43**

(Contd. of page 6)

### 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation:** Contact manufacturer for recycling information.

### 14 Transport information

· <b>14.1 UN-Number</b>	Void
· <b>DOT, ADR, ADN, IMDG, IATA</b>	Void
· <b>14.2 UN proper shipping name</b>	Void
· <b>DOT, ADR, ADN, IMDG, IATA</b>	Void
· <b>14.3 Transport hazard class(es)</b>	
· <b>DOT, ADR, ADN, IMDG, IATA</b>	Void
· <b>Class</b>	Void
· <b>14.4 Packing group</b>	Void
· <b>DOT, ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user:</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:</b>	Not applicable.

### 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**  
None of the ingredients is listed.
- **Section 313 (Specific toxic chemical listings):**  
All ingredients are listed.
- **TSCA (Toxic Substances Control Act):**  
All components have the value ACTIVE.
- **Hazardous Air Pollutants:**  
7439-92-1 lead
- **Proposition 65**
- **Chemicals known to cause cancer:**  
7440-02-0 nickel

(Contd. on page 8)

US

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 01/13/2026

Version - No. 1

Reviewed on 01/13/2026

**1.1 Trade name: eco M43**

(Contd. of page 7)

7440-38-2 arsenic

7439-92-1 lead

· **Chemicals known to cause reproductive toxicity for females:** \_\_\_\_\_

7439-92-1 lead

· **Chemicals known to cause reproductive toxicity for males:** \_\_\_\_\_

7439-92-1 lead

· **Chemicals known to cause developmental toxicity:** \_\_\_\_\_

7439-92-1 lead

· **Cancerogenity categories**· **EPA (Environmental Protection Agency):** \_\_\_\_\_

7440-50-8 copper: D

7440-66-6 zinc: D, I, II

7440-38-2 arsenic: A

7439-92-1 lead: B2

· **TLV (Threshold Limit Value established by ACGIH):** \_\_\_\_\_

7440-02-0 nickel: A5

7440-38-2 arsenic: A1

7439-92-1 lead: A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health):** \_\_\_\_\_

7440-02-0 nickel

7440-38-2 arsenic

· **Chemical safety assessment:** Void.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific article features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** ESG Affairs· **Contact:**

Dr. Stefan Priggemeyer

Phone +49 731 944 2794

Email: stefan.priggemeyer@wieland.com

us