

Page 1/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10


Reviewed on 05/19/2022

1 Identification

· Product identifier

- Trade name: Wieland-M10
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the article: Semi-finished product
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Wieland-Werke AG Graf-Arco-Str. 36 89079 Ulm
- · Information department: Associations & Management Systems stefan.priggemeyer@wieland.com
- Telephone number: +49 731 944 2794 (Monday Friday from 9 a.m. to 4 p.m.)

2 Hazard(s) identification



(Contd. on page 2)

¹¹⁵



(Contd. of page 1)

Page 2/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

· Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Metal in massive form.
- Material Code (CEN/TS 13388): CuZn10
- · Material number (CEN/TS 13388): CW501L
- · UNS-number: C22000

· Information:

The classifications listed below reflect the classification of the relevant alloying constituents and are only for information.

Mentioned percentages are references values.

Alloy components:

 7440-50-8 copper
 89.0-91.0%

 7440-66-6 zinc
 Balance%

 7440-02-0 nickel
 max. 0.3%

 ♦ Carc. 2, H351; STOT RE 1, H372; ♦ Skin Sens. 1, H317
 max. 0.05%

 ♦ Carc. 2, H351; Repr. 1A, H360
 max. 0.05%

4 First-aid measures

· Description of first aid measures

· General information:

First Aid information refer to any dust which is generated.

The mixture in solid form does not pose any significant health hazard. However, melting or activites which produce metal dust, smoke or fumes can cause that metal dust enter the body in harmful amounts.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water.
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

(Contd. on page 3)

[–] ús

(Contd. of page 2)

Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

• **Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

• Suitable extinguishing agents: Non-flammable. Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures: Not required.

- · Environmental precautions: Not required.
- Methods and material for containment and cleaning up: Collect the material and if necessary dispose it as waste according to section 13.
- Reference to other sections:
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Further information about storage conditions: Store in dry conditions.
- Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

US -

Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

Components with limit values that require monitoring at the workplace: Y440-50-8 copper PEL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume REL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume FLV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume, as Cu Y440-02-0 nickel PEL Long-term value: 1 mg/m³ *dusts and mists; **fume, as Cu Y440-02-0 nickel PEL Long-term value: 1 mg/m³ *dusts and mists; **fume, as Cu Y440-02-0 nickel PEL Long-term value: 0.015 mg/m³ *dusts and mists; **fume, as Cu Y440-02-0 nickel PEL Long-term value: 0.05 mg/m³ as Ni; See Pocket Guide App. A FLV Long-term value: 0.05* mg/m³ elemental, "inhalable fraction, A5, BEI Y439-92-1 lead PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: Y440-02-0 nickel BEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) Y30-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead		(Contd. of page
440-50-8 copper PEL Long-term value: 1* 0.1** mg/m³ as Cu "dusts and mists **fume REL Long-term value: 1* 0.2** mg/m³ as Cu "dusts and mists **fume TLV Long-term value: 1* 0.2** mg/m³ *dusts and mists, **fume; as Cu 440-02-0 nickel PEL Long-term value: 0.015 mg/m³ REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A TLV Long-term value: 0.05* mg/m³ elemental, "inhalable fraction, A5, BEI 439-92-1 lead PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 mgredients with biological limit values: 440-02-0 nickel SEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: wine Time: nost-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead SEI 200 µg/L Medium: wine Time: post-shift at end of workweek Parameter: Nickel (background)	Control parameters	
PEL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume REL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume FLV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu 7440-02-0 nickel PEL Long-term value: 1 mg/m³ REL Long-term value: 1.1* mg/m³ REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A FLV Long-term value: 0.05* mg/m³ elemental, *inhalable fraction, A5, BEI 7439-92-1 lead PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 mgredients with biological limit values: 7440-02-0 nickel 2EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: not critical Parameter: Nickel (background)	Components with limit values that require monitoring at the workplace:	
as Ču *dusts and mists **fume REL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume IV Long-term value: 1 0.2** mg/m³ *dusts and mists; **fume; as Cu *440-02-0 nickel PEL Long-term value: 1 mg/m³ REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A IV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI *439-92-1 lead PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *a-hr TWA; See PocketGuide App.C IV Long-term value: 0.05* mg/m³ *a di norganic compds., as Pb; BEI, A3 ngredients with biological limit values: *440-02-0 nickel SEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) *439-92-1 lead SEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	7440-50-8 copper	
as Ču *dusts and mists **fume [LV Long-term value: 1 * 0.2** mg/m ³ *dusts and mists; **fume; as Cu *440-02-0 nickel PEL Long-term value: 1 mg/m ³ REL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A [LV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI *439-92-1 lead PEL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: *440-02-0 nickel SEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) *439-92-1 lead SEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	PEL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
*dušts and mists; **fume; as Cu *440-02-0 nickel PEL Long-term value: 1 mg/m ³ REL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A TLV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI *439-92-1 lead PEL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C TLV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: *440-02-0 nickel BEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) *439-92-1 lead BEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	REL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume	
PEL Long-term value: 1 mg/m³ REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A ILV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI /439-92-1 lead PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *shr TWA; See PocketGuide App.C FLV Long-term value: 0.05* mg/m³ *ahr TWA; See PocketGuide App.C FLV Long-term value: 0.05* mg/m³ *ahr TWA; See PocketGuide App.C FLV Long-term value: 0.05* mg/m³ *ahr TWA; See PocketGuide App.C FLV Long-term value: 0.05* mg/m³ *ahr TWA; See PocketGuide App.C FLV Long-term value: 0.05* mg/m³ *ahr TWA; See PocketGuide App.C FLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: /440-02-0 nickel 3EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) /439-92-1 lead 3EI 200 μg/L	TLV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu	
REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A FLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI Y439-92-1 lead PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: Y440-02-0 nickel 3EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) X30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) X439-92-1 lead SEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	7440-02-0 nickel	
as Ni; See Pocket Guide App. A fLV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI /439-92-1 lead PEL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C fLV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: /440-02-0 nickel SEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead SEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	PEL Long-term value: 1 mg/m³	
elemental, *inhalable fraction, A5, BEI 7439-92-1 lead PEL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C TLV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: 7440-02-0 nickel SEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead SEI 20 µg/L Medium: blood Time: not critical Parameter: Lead	REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A	
PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 REL Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C fLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: /440-02-0 nickel BEI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 320 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) /439-92-1 lead BEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI	
see 29 CFR 1910.1025 REL Long-term value: 0.05 mg/m ³ *8-hr TWA ;See PocketGuide App.C FLV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: /440-02-0 nickel 3EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) /439-92-1 lead 3EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	7439-92-1 lead	
 8-hr TWA ;See PocketGuide App.C fLV Long-term value: 0.05 mg/m³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: 7440-02-0 nickel 3EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead 3EI 200 µg/L Medium: blood Time: not critical Parameter: Lead 	PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025	
and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: 7440-02-0 nickel BEI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead	REL Long-term value: 0.05 mg/m³ *8-hr TWA ;See PocketGuide App.C	
7440-02-0 nickel 3EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) Y439-92-1 lead 3EI 200 μg/L Medium: blood Time: not critical Parameter: Lead	TLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3	
 3EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead 3EI 200 μg/L Medium: blood Time: not critical Parameter: Lead 	Ingredients with biological limit values:	
Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead	7440-02-0 nickel	
Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead BEI 200 µg/L Medium: blood Time: not critical Parameter: Lead	BEI 5 μg/L	
Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead BEI 200 µg/L Medium: blood Time: not critical Parameter: Lead		
30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead 3EI 200 μg/L Medium: blood Time: not critical Parameter: Lead		
Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead	Parameter: Nickel (background)	
Time: post-shift at end of workweek Parameter: Nickel (background) 7439-92-1 lead BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead	30 μg/L	
Parameter: Nickel (background) 7439-92-1 lead BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead		
7439-92-1 lead BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead		
BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead		
Medium: blood Time: not critical Parameter: Lead		
Time: not critical Parameter: Lead		
Parameter: Lead		
(Cond. of page		(Contd. on page

Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

Additional Occupational Exposure Limit Values for possible hazards during processing: (1314-13-2 zinc oxide PEL Long-term value: 15* 5** mg/m³		(Contd. of page
PEL Long-term value: 15* 5** mg/m ³ total dust **respirable fraction and fume REL Short-term value: 0** mg/m ³ Long-term value: 15* mg/m ³ Ceiling limit value: 15° mg/m ³ Tube 15' mg/m ³ total only **fume TLV Short-term value: 10* mg/m ³ Long-term value: 2* mg/m ³ * are respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective end hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Protective of hands: Protection of hands: Protection of hands: Protection or leather). Eye protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. Change in condition Meting point/Boiling range: Undetermined. Not applicable. Danger of explosion: Protectioe clothing resert an explosion hazard.	· Additional Occupational Exposure Limit Va	lues for possible hazards during processing:
"total dust **respirable fraction and fume REL Short-term value: 10** mg/m³ Long-term value: 5 mg/m³ "dust only **fume TLV Short-term value: 10* mg/m³ Long-term value: 2* mg/m³ "as respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective gogles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depen	1314-13-2 zinc oxide	
REL Short-term value: 10** mg/m ³ Long-term value: 15 mg/m ³ 'dust only **fume TLV Short-term value: 10* mg/m ³ Long-term value: 2* mg/m ³ *as respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection of hands: Protection of hands: Protection: Protection: Protection: Protection: Protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Breas usuable protective clothing, depending upon how the semis are further processed. Body protection: Protection: Protection: Protection: Protection: Protection: Breas yellow Odor: Odor threshold: Change in condition Melting point/Melting range: Danger of explosion: Protect ones protection: Protection: Protection: Protection: Protection: Protection: Danger of explosion: Protection: Product does not present an explosion hazard.	PEL Long-term value: 15* 5** mg/m³	
Long-term value: 5 mg/m ³ Ceiling limit value: 15* mg/m ³ *dust only **fume TLV Short-term value: 2' mg/m ³ *as respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protection: Protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing. Color: Brass yellow Odor: Odor threshold: Not determined. Change in condition Melting point/Melting range: Danger of explosion: Danger	*total dust **respirable fraction and fume	
Ceiling limit value: 15 [°] mg/m ³ *dust only **fume TLV Short-term value: 10 * mg/m ³ Long-term value: 2* mg/m ³ *as respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protection: Protection: Protection: Protection: Protection: Form: General Information Appearance: Form: Solid Color: Odor insolve the semis are further processed. Odor insolve the semises Odor threshold: Odor insolve the semises Odor insolve the		
*dust only **fume TLV Short-term value: 10* mg/m³ Long-term value: 2* mg/m³ *as respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Form: Solid Color:		
TLV Short-term value: 10* mg/m³ Long-term value: 2* mg/m³ *as respirable fraction • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective equipment: General protective olothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protective of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective glogels are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. Change in condition Metting point/Melting range: Metting point/Boiling		
Long-term value: 2* mg/m³ *as respirable fraction Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection of hands: Protection of leather). Eye protection: Protective glogles are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protection of bands: Protection: Protective glogles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Color: Brass yellow Odor: Odor: Odor: Odor: Color: Brass yellow Odor: Color: Brass pellow Odor: Color: Brass pellow Odor: Color: Brass yellow Odor: Color: Brass yellow Color: Change in condition Melting point/Melting range: Undetermined. Fash point: Not applicable. Danger of explosion: Product dees not present an explosion hazard.		
*as respirable fraction *Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection of hands: Protection of leather). Eye protection: Protection or leather). Eye protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Odor breshold: Not determined. Change in condition Melting point/Melting range: Undetermined. Change in condition Melting point/Melting range: Data the protection of the process of the protection. Product does not present an explosion hazard.		
Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Physical and chemical properties General Information Appearance: Form: Color: Dotor: Do		
Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing and chemical properties General Information Appearance: Form: Solid Color: Odorless Odor threshold: Not determined. Change in condition Meting point/Boiling range: Undetermined. Change in condition Meting point/Boiling rang	·	alid during the creation were used as basis
Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection of hands: Protection gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective gogles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. * Change in condition Melting point/Melting range: Melting point/Boiling range: Undetermined. * Change in condition Not applicable. Planger of explosion: Product does not present an explosion hazard. <td></td> <td></td>		
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection of hands: Protection gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. * Change in condition Melting point/Melting range: Melting point/Boiling range: Undetermined. * Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard.		
Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection: Protection: Protection: Protection: Protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. * Change in condition 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. * Flash point: Not applicable. Danger of explosion: Product	· General protective and hygienic measures:	
Store protective clothing separately. Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information on basic physical and chemical properties General Information Appearance: Form: Color: Dange in condition Melting point/Beiling range: Flash point: Danger of explosion: Product does not present an explosion hazard.		
Do not inhale dust / smoke / mist. Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protection of hands: Protection: Protection: Protection: Wear suitable protective clothing, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Color: Ddor: Odor threshold: Change in condition Melting point/Melting range: Danger of explosion: Product does not present an explosion hazard.		work.
 Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Color: Solid Color: Solid Color: Solid Color: Solid Color: Solid Color: Solid Color: Brass yellow Odor threshold: Not determined. Change in condition Melting point/Melting range: Boiling point/Boiling range: Danger of explosion: Not applicable. Product does not present an explosion hazard. 		
 Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Boiling range: Difference: Flash point: Danger of explosion: Product does not present an explosion hazard. 		ial gas mask when work-place-limits are exceeded
Protective gloves are recommended, depending upon how the semis are further processed (material or gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties Physical and chemical and chemical properties General Information Appearance: Form: Color:	• • •	lai gas mask when work-place-limits are exceeded.
gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties Physical and chemical properties General Information Appearance: Form: Color: Solid Color: Odor threshold: Solid Color: Change in condition Melting point/Melting range: Difference: Product does not present an explosion hazard.		ng upon how the semis are further processed (material o
Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties Physical and chemical properties General Information Appearance: Form: Color: Solid Color: S	gloves: neoprene or leather).	
Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. * Change in condition 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. * Flash point: Not applicable. Panger of explosion: Product does not present an explosion hazard.		
Wear suitable protective clothing, depending upon how the semis are further processed. Physical and chemical properties Information on basic physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. * Change in condition 1005-1025 °C (1841-1877 °F) Boiling point/Beiling range: Undetermined. * Flash point: Not applicable. Panger of explosion: Product does not present an explosion hazard.		ling upon how the semis are further processed.
 Physical and chemical properties Information on basic physical and chemical properties General Information Appearance: Form: Color: Odor: Odor: Odor threshold: Not determined. Change in condition Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Product does not present an explosion hazard. 		inon how the semis are further processed
 Information on basic physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. Change in condition Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Product does not present an explosion hazard. 		
 Information on basic physical and chemical properties General Information Appearance: Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. Change in condition Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Product does not present an explosion hazard. 		
 General Information Appearance: Form: Solid Brass yellow Odor: Odorless Odor threshold: Not determined. Change in condition Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Product does not present an explosion hazard. 	Physical and chemical properties	
 Appearance: Form: Solid Color: Odor: Odorless Odor threshold: Odor threshold: Not determined. Change in condition Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Product does not present an explosion hazard. 		Il properties
Form: Solid Color: Brass yellow Odor: Odorless Odor threshold: Not determined. * Change in condition Not determined. Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. • Flash point: Not applicable. • Danger of explosion: Product does not present an explosion hazard.		
Color: Brass yellow Odor: Odorless Odor threshold: Not determined. Change in condition Not determined. Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard.	· Appearance:	
 Odor: Odor threshold: Odor threshold: Change in condition Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Product does not present an explosion hazard. 	••	
Odor threshold: Not determined. Change in condition 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. Flash point: Not applicable. Danger of explosion: Product does not present an explosion hazard.	Form:	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Danger of explosion: 1005-1025 °C (1841-1877 °F) Undetermined. Not applicable. Product does not present an explosion hazard. 	Form: Color:	Brass yellow
Melting point/Melting range: 1005-1025 °C (1841-1877 °F) Boiling point/Boiling range: Undetermined. • Flash point: Not applicable. • Danger of explosion: Product does not present an explosion hazard.	Form: Color: • Odor:	Brass yellow Odorless
Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Danger of explosion:Product does not present an explosion hazard.	Form: Color: · Odor: · Odor threshold:	Brass yellow Odorless
· Flash point:Not applicable.· Danger of explosion:Product does not present an explosion hazard.	Form: Color: • Odor: • Odor threshold: • Change in condition	Brass yellow Odorless Not determined.
• Danger of explosion: Product does not present an explosion hazard.	Form: Color: • Odor: • Odor threshold: • Change in condition Melting point/Melting range:	Brass yellow Odorless Not determined. 1005-1025 °C (1841-1877 °F)
	Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range:	Brass yellow Odorless Not determined. 1005-1025 °C (1841-1877 °F) Undetermined.
	Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point:	Brass yellow Odorless Not determined. 1005-1025 °C (1841-1877 °F) Undetermined. Not applicable.



(Contd. of page 5)

Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

	(Conta. of page 3
· Solubility in / Miscibility with wate	er at 20 °C (68
°F):	Not soluble.
· Solvent separation test	
VOC content:	0.00 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity: Not applicable.
- · Chemical stability: Not applicable.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

When used and handled according to specifications, the article does not have any harmful effects to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7440-02-0 nickel: 2B 7439-92-1 lead: 2B

· NTP (National Toxicology Program)

7440-02-0 nickel: R 7439-92-1 lead: R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

(Contd. of page 6)

12 Ecological information

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.
- Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Contact manufacturer for recycling information.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	Void	
 UN proper shipping name DOT, ADR, IMDG, IATA 	Void	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Void	
 Packing group DOT, ADR, IMDG, IATA 	Void	
· Environmental hazards:	Not applicable.	
· Special precautions for user:	Not applicable.	
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code: 	II of Not applicable.	

(Contd. on page 8)

Page 8/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

(Contd. of page 7)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixtur	Э
Sara	
Section 355 (extremely hazardous substances):	
None of the ingredients is listed. Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants:	
7439-92-1 lead	
Proposition 65 Chemicals known to cause cancer:	
7440-02-0 nickel	
7439-92-1 lead Chemicals known to cause reproductive toxicity for females:	
7439-92-1 lead Chemicals known to cause reproductive toxicity for males:	
7439-92-1 lead Chemicals known to cause developmental toxicity:	
7439-92-1 lead	
Cancerogenity categories EPA (Environmental Protection Agency):	
7440-50-8 copper: D	
7440-66-6 zinc: D, I, II	
7439-92-1 lead: B2	
TLV (Threshold Limit Value established by ACGIH):	
7440-02-0 nickel: A5	
7439-92-1 lead: A3	
NIOSH-Ca (National Institute for Occupational Safety and Health):	
7440-02-0 nickel	
Chemical safety assessment: Void.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific article features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Associations & Management Systems

(Contd. on page 9)

US



(Contd. of page 8)

119

Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/19/2022

Version - No. 10

Reviewed on 05/19/2022

Trade name: Wieland-M10

· Contact:

Dr. Stefan Priggemeyer

Email: stefan.priggemeyer@wieland.com
** Data compared to the previous version altered.