

Page 1/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11


Reviewed on 05/23/2022

1 Identification

· Product identifier

- Trade name: Wieland-M38
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the article: Semi-finished product
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Wieland-Werke AG Graf-Arco-Str. 36 89079 Ulm
- · Information department: Associations & Management Systems stefan.priggemeyer@wieland.com
- Telephone number: +49 731 944 2794 (Monday Friday from 9 a.m. to 4 p.m.)

2 Hazard(s) identification



(Contd. on page 2)

¹¹⁵



(Contd. of page 1)

Page 2/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

· Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · **Description:** Metal in massive form.
- Material Code (CEN/TS 13388): CuZn37
- · Material number (CEN/TS 13388): CW508L
- · UNS-number: C27400, C27200

· Information:

The classifications listed below reflect the classification of the relevant alloying constituents and are only for information.

Mentioned percentages are references values.

Alloy components:

 7440-50-8 copper
 62.0-64.0%

 7440-66-6 zinc
 Balance%

 7440-02-0 nickel
 max. 0.3%

 ♦ Carc. 2, H351; STOT RE 1, H372; ♦ Skin Sens. 1, H317
 max. 0.09%

 ♦ Carc. 2, H351; Repr. 1A, H360
 max. 0.09%

4 First-aid measures

· Description of first aid measures

· General information:

First Aid information refer to any dust which is generated.

The mixture in solid form does not pose any significant health hazard. However, melting or activites which produce metal dust, smoke or fumes can cause that metal dust enter the body in harmful amounts.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water.
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

(Contd. on page 3)

⁻ US

(Contd. of page 2)

Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

• **Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: Non-flammable. Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures: Not required.

- · Environmental precautions: Not required.
- Methods and material for containment and cleaning up: Collect the material and if necessary dispose it as waste according to section 13.
- Reference to other sections:
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Further information about storage conditions: Store in dry conditions.

• Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

US -

Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

omponents with limit values that require monitoring at the workplace: 440-50-8 copper EL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume EL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume LV Long-term value: 1* 0.2** mg/m³ rdusts and mists **fume; as Cu 440-02-0 nickel EL Long-term value: 1 mg/m³ EL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 Start TW A; See PocketGuide App.C LV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 Start TW A; See PocketGuide App.C LV Long-term value: 0.05* mg/m³ Yu A; See PocketGuide App.C LV Long-term value: 0.05* mg/m³ Yu A; See PocketGuide		(Contd. of page
440-50-8 copper EL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume EL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume LV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu 440-02-0 nickel EL Long-term value: 0.015 mg/m³ *dusts and mists; **fume; as Cu 440-02-0 nickel EL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A LV Long-term value: 0.05* mg/m³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 EL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 EL Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	Control parameters	
EL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume EL Long-term value: 1* 0.2** mg/m ³ as Cu *dusts and mists **fume LV Long-term value: 1 * 0.2** mg/m ³ *dusts and mists; **fume; as Cu 440-02-0 nickel EL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A LV Long-term value: 0.015 mg/m ³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App. C LV Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App. C LV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 mgredients with biological limit values: 440-02-0 nickel EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 39 9 /L Medium: biological Limit value Parameter: Nickel (background) 39 9 /L Medium: biological EI 200 μg/L Medium: biological EI 200 μg/L	Components with limit values that require monitoring at the workplace:	
as Ču *dusts and mists **fume EL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume EV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu 440-02-0 nickel EL Long-term value: 1 mg/m³ EL Long-term value: 1 mg/m³ EL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 *EL Long-term value: 0.05* mg/m³ *shr TWA; See PocketGuide App.C LV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 tgredients with biological limit values: 440-02-0 nickel EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 33 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: not critical Parameter: Lead	7440-50-8 copper	
as Ču *dusts and mists **fume LV Long-term value: 1* 0.2** mg/m ³ *dusts and mists; **fume; as Cu 440-02-0 nickel EL Long-term value: 1 mg/m ³ :EL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 :EL Long-term value: 0.05* mg/m ³ *aed inorganic compds., as Pb; BEI, A3 mgredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	PEL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
*dusts and mists; **fume; as Cu 440-02-0 nickel EL Long-term value: 1 mg/m ³ :EL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 :EL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 trgredients with biological limit values: 440-02-0 nickel EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 μg/L Medium: blood Time: not critical Parameter: Lead	REL Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume	
EL Long-term value: 1 mg/m ³ IEL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 IEL Long-term value: 0.05* mg/m ³ *a-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 hgredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	TLV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu	
 EL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 EL Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 hgredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead 	7440-02-0 nickel	
 EL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A LV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025 EL Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3 hgredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead 	PEL Long-term value: 1 mg/m³	
elemental, *inhalable fraction, A5, BEI 439-92-1 lead EL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 EL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 hgredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	REL Long-term value: 0.015 mg/m³	
EL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 EL Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 ngredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	TLV Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI	
see 29 CFR 1910.1025 HEL Long-term value: 0.05 mg/m ³ *8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05* mg/m ³ *and inorganic compds., as Pb; BEI, A3 the predients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead	7439-92-1 lead	
 8-hr TWA ;See PocketGuide App.C LV Long-term value: 0.05 mg/m³ *and inorganic compds., as Pb; BEI, A3 hgredients with biological limit values: 440-02-0 nickel EI 5 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 µg/L Medium: blood Time: not critical Parameter: Lead 	PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025	
and inorganic compds., as Pb; BEI, A3 agredients with biological limit values: 440-02-0 nickel EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 μg/L Medium: blood Time: not critical Parameter: Lead	REL Long-term value: 0.05 mg/m³ *8-hr TWA ;See PocketGuide App.C	
440-02-0 nickel EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 μg/L Medium: blood Time: not critical Parameter: Lead	TLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3	
440-02-0 nickel EI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead EI 200 μg/L Medium: blood Time: not critical Parameter: Lead	Ingredients with biological limit values:	
Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead El 200 µg/L Medium: blood Time: not critical Parameter: Lead	7440-02-0 nickel	
Time: post-shift at end of workweek Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead El 200 µg/L Medium: blood Time: not critical Parameter: Lead	BEI 5 μg/L	
Parameter: Nickel (background) 30 µg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead El 200 µg/L Medium: blood Time: not critical Parameter: Lead		
30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead El 200 μg/L Medium: blood Time: not critical Parameter: Lead		
Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead El 200 μg/L Medium: blood Time: not critical Parameter: Lead	Parameter: Nickel (background)	
Time: post-shift at end of workweek Parameter: Nickel (background) 439-92-1 lead El 200 μg/L Medium: blood Time: not critical Parameter: Lead	30 μg/L	
Parameter: Nickel (background) 439-92-1 lead El 200 µg/L Medium: blood Time: not critical Parameter: Lead		
439-92-1 lead El 200 μg/L Medium: blood Time: not critical Parameter: Lead		
El 200 µg/L Medium: blood Time: not critical Parameter: Lead		
Medium: blood Time: not critical Parameter: Lead		
Time: not critical Parameter: Lead		
Parameter: Lead		
(Contd. on page		
		(Contd. on page

Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

	t Values for possible hazards during processing:
1314-13-2 zinc oxide PEL Long-term value: 15* 5** mg/m ³	
*total dust **respirable fraction and fur	me
REL Short-term value: 10** mg/m ³	
Long-term value: 5 mg/m ³	
Ceiling limit value: 15* mg/m ³	
*dust only **fume	
TLV Short-term value: 10* mg/m ³ Long-term value: 2* mg/m ³	
*as respirable fraction	
	e valid during the creation were used as basis.
· Exposure controls	-
Personal protective equipment:	
· General protective and hygienic measur	
Keep away from foodstuffs, beverages and Wash hands before breaks and at the end	
Store protective clothing separately.	UI WUIK.
Do not inhale dust / smoke / mist.	
· Breathing equipment: Use a suitable indu	ustrial gas mask when work-place-limits are exceeded.
Protection of hands:	
	nding upon how the semis are further processed (material c
gloves: neoprene or leather).	
• Eye protection: Protective goggles are recommended, depe	ending upon how the semis are further processed.
• Eye protection: Protective goggles are recommended, depe • Body protection:	
• Eye protection: Protective goggles are recommended, depe • Body protection:	ending upon how the semis are further processed. ng upon how the semis are further processed.
• Eye protection: Protective goggles are recommended, depe • Body protection: Wear suitable protective clothing, dependin	ng upon how the semis are further processed.
• Eye protection: Protective goggles are recommended, depe • Body protection:	ng upon how the semis are further processed.
• Eye protection: Protective goggles are recommended, depe • Body protection: Wear suitable protective clothing, dependin • Physical and chemical properties • Information on basic physical and chem	ng upon how the semis are further processed.
Eye protection: Protective goggles are recommended, deper- Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information	ng upon how the semis are further processed.
Eye protection: Protective goggles are recommended, deperimended, depended, depended	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemical chemical information Appearance: Form: 	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemical environmentation Appearance: Form: Color: 	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemical chemical information Appearance: Form: 	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemediate General Information Appearance: Form: Color: Odor: 	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperation: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chemical environment of the second sec	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemediate General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: 	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemediate in General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: 	ng upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, depending Physical and chemical properties Information on basic physical and chemediate General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: 	ng upon how the semis are further processed.



(Contd. of page 5)

Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

	(Conta. of page (
 Solubility in / Miscibility with wat 	ter at 20 °C (68
°F):	Not soluble.
· Solvent separation test	
VOC content:	0.00 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity: Not applicable.
- · Chemical stability: Not applicable.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

When used and handled according to specifications, the article does not have any harmful effects to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7440-02-0 nickel: 2B 7439-92-1 lead: 2B

· NTP (National Toxicology Program)

7440-02-0 nickel: R 7439-92-1 lead: R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

(Contd. of page 6)

12 Ecological information

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.
- Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Contact manufacturer for recycling information.

14 Transport information

•		
· UN-Number · DOT, ADR, IMDG, IATA	Void	
 [.] UN proper shipping name [.] DOT, ADR, IMDG, IATA 	Void	
· Transport hazard class(es)		
[·] DOT, ADR, ADN, IMDG, IATA [·] Class	Void	
 Packing group DOT, ADR, IMDG, IATA 	Void	
· Environmental hazards:	Not applicable.	
· Special precautions for user:	Not applicable.	
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code: 	x II of Not applicable.	

(Contd. on page 8)

Page 8/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

(Contd. of page 7)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara
Section 355 (extremely hazardous substances):
None of the ingredients is listed. Section 313 (Specific toxic chemical listings):
All ingredients are listed.
TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
Hazardous Air Pollutants:
7439-92-1 lead
Proposition 65 Chemicals known to cause cancer:
7440-02-0 nickel
7439-92-1 lead Chemicals known to cause reproductive toxicity for females:
7439-92-1 lead Chemicals known to cause reproductive toxicity for males:
7439-92-1 lead Chemicals known to cause developmental toxicity:
7439-92-1 lead
Cancerogenity categories <u>EPA (Environmental Protection Agency):</u> 7440-50-8 copper: D
7440-66-6 zinc: D, I, II
7439-92-1 lead: B2
TLV (Threshold Limit Value established by ACGIH):
7440-02-0 nickel: A5
7439-92-1 lead: A3
NIOSH-Ca (National Institute for Occupational Safety and Health): 7440-02-0 nickel
Chemical safety assessment: Void.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific article features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Associations & Management Systems

(Contd. on page 9)

US



(Contd. of page 8)

119

Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing date 05/23/2022

Version - No. 11

Reviewed on 05/23/2022

Trade name: Wieland-M38

· Contact:

Dr. Stefan Priggemeyer

Email: stefan.priggemeyer@wieland.com
** Data compared to the previous version altered.