

Page 1/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

1 Identification

· Product identifier

- Trade name: Wieland-N48
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the article: Semi-finished product
- · Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:** Wieland-Werke AG Graf-Arco-Str. 36 89079 Ulm
- Information department: Associations & Management Systems stefan.priggemeyer@wieland.com
- Telephone number: +49 731 944 2794 (Monday Friday from 9 a.m. to 4 p.m.)

2 Hazard(s) identification

· Classification of the substance or mixture:

GHS

GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Repr. 1A H360 May damage fertility or the unborn child.

STOT RE 1 H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms: GHS07, GHS08
- · Signal word: Danger
- · Hazard statements:
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H360 May damage fertility or the unborn child.
- H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)



Page 2/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

(Contd. of page 1)

Trade name: Wieland-N48

P363	Wash contaminated clothing before reuse.
------	--

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

• Results of PBT and vPvB assessment

· PBT: Not applicable to metals.

vPvB: Not applicable to metals.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Metal in massive form.
- · Material Code (CEN/TS 13388): CuNi12Zn38Mn5b2
- · Material number (CEN/TS 13388): CW407J
- · UNS-number: -

· Information:

The classifications listed below reflect the classification of the relevant alloying constituents and are only for information.

Mentioned percentages are references values.

Alloy components:

7440-50-8 copper	42-45%
7440-66-6 zinc	Balance%
7440-02-0 nickel	11-13%
🚸 Carc. 2, H351; STOT RE 1, H372; 🚸 Skin Sens. 1, H317	
7439-96-5 manganese	4.5-6.0%
7439-92-1 lead	1.0-2.5%
🚸 Carc. 2, H351; Repr. 1A, H360	

4 First-aid measures

· Description of first aid measures

· General information:

First Aid information refer to any dust which is generated.

The mixture in solid form does not pose any significant health hazard. However, melting or activites which produce metal dust, smoke or fumes can cause that metal dust enter the body in harmful amounts.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)



(Contd. of page 2)

Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

Trade name: Wieland-N48

- After swallowing: Rinse out mouth and then drink plenty of water.
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Non-flammable. Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- · Environmental precautions: Not required.
- **Methods and material for containment and cleaning up:** Collect the material and if necessary dispose it as waste according to section 13.
- Reference to other sections:
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Further information about storage conditions: Store in dry conditions.
- **Specific end use(s):** No further relevant information available.
- 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

us -

wieland

Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

Trade name: Wieland-N48

	(Contd. of page
Control parameters	
Components with limit values that require monitoring at the workplace:	
7440-50-8 copper	
PEL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
REL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
TLV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu	
7440-02-0 nickel	
PEL Long-term value: 1 mg/m³	
REL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A	
TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI	
7439-96-5 manganese	
PEL Ceiling limit value: 5 mg/m³ as Mn	
REL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ fume, as Mn	
TLV Long-term value: 0.02* 0.1** mg/m³ as Mn; A4, *respirable **inhalable fraction	
7439-92-1 lead	
PEL Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025	
REL Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C	
TLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3	
Ingredients with biological limit values:	
7440-02-0 nickel	
BEI 5 µg/L Medium: urine	
Time: post-shift at end of workweek Parameter: Nickel (background)	
30 μg/L	
Medium: urine Time: post-shift at end of workweek	
Parameter: Nickel (background)	
	(Contd. on page

- US -

wieland

Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

Trade name: Wieland-N48

(Contd. of page 4) 7439-92-1 lead BEI 200 µg/L Medium: blood Time: not critical Parameter: Lead · Additional Occupational Exposure Limit Values for possible hazards during processing: 1314-13-2 zinc oxide PEL Long-term value: 15* 5** mg/m³ *total dust **respirable fraction and fume REL Short-term value: 10** mg/m³ Long-term value: 5 mg/m³ Ceiling limit value: 15* mg/m³ *dust only **fume TLV Short-term value: 10* mg/m³ Long-term value: 2* mg/m³ *as respirable fraction • Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale dust / smoke / mist. • Breathing equipment: Use a suitable industrial gas mask when work-place-limits are exceeded. · Protection of hands: Protective gloves are recommended, depending upon how the semis are further processed (material of gloves: neoprene or leather). Eye protection: Protective goggles are recommended, depending upon how the semis are further processed. Body protection: Wear suitable protective clothing, depending upon how the semis are further processed. 9 Physical and chemical properties · Information on basic physical and chemical properties General Information · Appearance: Form: Solid Color: Silver-grey · Odor: Odorless · Odor threshold: Not determined. · Change in condition

900-950 °C (1652-1742 °F)

Mange in condition
Melting point/Melting range:

(Contd. on page 6)

US ·

Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

Trade name: Wieland-N48

Undetermined.	
Not applicable	
Not applicable.	
Product does not present an explosion hazard.	
8.3 g/cm³ (69.2635 lbs/gal)	
58 J	
Not soluble.	
0.00 %	
No further relevant information available.	

10 Stability and reactivity

- · Reactivity: Not applicable.
- · Chemical stability: Not applicable.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

• Acute toxicity: Based on available data, the classification criteria are not met.

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
 When used and handled according to specifications, the article does not have any harmful effects to our experience and the information provided to us.
 - · Carcinogenic categories
 - · IARC (International Agency for Research on Cancer)
 - 7440-02-0 nickel: 2B 7439-92-1 lead: 2B
 - · NTP (National Toxicology Program)
 - 7440-02-0 nickel: R 7439-92-1 lead: R

(Contd. on page 7)

US

wieland

Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

Trade name: Wieland-N48

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Aquatic toxicity: No further relevant information available.

- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.
- · Other adverse effects: No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Contact manufacturer for recycling information.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	Void	
 UN proper shipping name DOT, ADR, IMDG, IATA 	Void	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
Class	Void	
· Packing group		
· DOT, ADR, IMDG, IATA	Void	
· Environmental hazards:	Not applicable.	
· Special precautions for user:	Not applicable.	
		(Contd. on page

(Contd. of page 6)

-) US-



(Contd. of page 7)

Page 8/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

Trade name: Wieland-N48

 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the se Sara	
Section 355 (extremely hazardous substances):	
None of the ingredients is listed. Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants:	
7439-96-5 manganese	
7439-92-1 lead	
Proposition 65	
Chemicals known to cause cancer:	
7440-02-0 nickel	
7439-92-1 lead	
7439-92-1 lead Chemicals known to cause reproductive toxicity for males:	
7439-92-1 lead	
7439-92-1 lead	
Cancerogenity categories	
EPA (Environmental Protection Agency):	
7440-50-8 copper: D	
7440-66-6 zinc: D, I, II	
7439-96-5 manganese: D	
7439-92-1 lead: B2	
TLV (Threshold Limit Value established by ACGIH):	
7440-02-0 nickel: A5	
7439-92-1 lead: A3	
NIOSH-Ca (National Institute for Occupational Safety and Health):	
7440-02-0 nickel	
	(Contd. on page



Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing date 08/25/2022

Version - No. 11

Reviewed on 08/25/2022

(Contd. of page 8)

119

Trade name: Wieland-N48

· Chemical safety assessment: Void.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific article features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Associations & Management Systems
- · Contact:

Dr. Stefan Priggemeyer

Email: stefan.priggemeyer@wieland.com

* Data compared to the previous version altered.