

Page 1/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

1 Identification

· Product identifier

- · Trade name: Wieland-Z62
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the article: Semi-finished product
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Wieland-Werke AG Graf-Arco-Str. 36 89079 Ulm
- Information department: Associations & Management Systems stefan.priggemeyer@wieland.com
- Telephone number: +49 731 944 2794 (Monday Friday from 9 a.m. to 4 p.m.)

2 Hazard(s) identification

Classification of the substance or mixture:

GHS08 Health hazard

- Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
- Repr. 1A H360 May damage fertility or the unborn child.

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms: GHS07, GHS08
- · Signal word: Danger
- · Hazard statements:
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H360 May damage fertility or the unborn child.
- · Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)



(Contd. of page 1)

Page 2/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

· Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · **Description:** Metal in massive form.
- Material Code (CEN/TS 13388): -
- Material number (CEN/TS 13388): -
- · UNS-number: C37710

· Information:

The classifications listed below reflect the classification of the relevant alloying constituents and are only for information.

Mentioned percentages are references values.

Alloy components:

4 First-aid measures

· Description of first aid measures

· General information:

First Aid information refer to any dust which is generated.

The mixture in solid form does not pose any significant health hazard. However, melting or activites which produce metal dust, smoke or fumes can cause that metal dust enter the body in harmful amounts.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water.
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

(Contd. on page 3)

⁻ US



Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

(Contd. of page 2)

Trade name: Wieland-Z62

• **Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: Non-flammable. Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures: Not required.

- · Environmental precautions: Not required.
- **Methods and material for containment and cleaning up:** Collect the material and if necessary dispose it as waste according to section 13.
- Reference to other sections:
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Further information about storage conditions: Store in dry conditions.
- Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

	(Contd. of page 3
Control parameters	
Components with limit values that require monitoring at the workplace:	
7440-50-8 copper	
PEL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
REL Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume	
TLV Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu	
7439-92-1 lead	
PEL Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025	
REL Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C	
TLV Long-term value: 0.05* mg/m³ *and inorganic compds., as Pb; BEI, A3	
7440-02-0 nickel	
PEL Long-term value: 1 mg/m³	
REL Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A	
TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI	
Ingredients with biological limit values:	
7439-92-1 lead	
BEI 200 μg/L Medium: blood Time: not critical Parameter: Lead	
7440-02-0 nickel	
BEI 5 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background)	
30 μg/L Medium: urine Time: post-shift at end of workweek Parameter: Nickel (background)	(Contd. on page 5

Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

	(Contd. of page 4
· Additional Occupational Exposure Limit	Values for possible hazards during processing:
1314-13-2 zinc oxide	
PEL Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction and fun	ne
REL Short-term value: 10** mg/m ³ Long-term value: 5 mg/m ³ Ceiling limit value: 15* mg/m ³ *dust only **fume	
TLV Short-term value: 10* mg/m³ Long-term value: 2* mg/m³ *as respirable fraction	
· Additional information: The lists that were	e valid during the creation were used as basis.
• Protection of hands: Protective gloves are recommended, deper	feed.
Body protection:	ending upon how the semis are further processed. Ig upon how the semis are further processed.
• Eye protection: Protective goggles are recommended, depe • Body protection:	g upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, depersion Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem 	g upon how the semis are further processed.
Eye protection: Protective goggles are recommended, dependent Body protection: Wear suitable protective clothing, dependin Physical and chemical properties	g upon how the semis are further processed.
 Eye protection: Protective goggles are recommended, dependent Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: 	ical properties
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: 	ical properties Solid Brass yellow
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: Odor: 	ical properties Solid Brass yellow Odorless
 Eye protection: Protective goggles are recommended, deperations Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: 	ical properties Solid Brass yellow
 Eye protection: Protective goggles are recommended, deperation: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition 	ical properties Solid Brass yellow Odorless Not determined.
 Èye protection: Protective goggles are recommended, deperative goggles are recommended, deperative solution. Body protection: Wear suitable protective clothing, dependin Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: 	ical properties Solid Brass yellow Odorless Not determined. 880-890 °C (1616-1634 °F)
 Eye protection: Protective goggles are recommended, deperation: Wear suitable protective clothing, dependin Physical and chemical properties Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: 	ical properties Solid Brass yellow Odorless Not determined. 880-890 °C (1616-1634 °F) Undetermined.
 Eye protection: Protective goggles are recommended, deperations: Wear suitable protective clothing, dependin Physical and chemical properties Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: 	ical properties Solid Brass yellow Odorless Not determined. 880-890 °C (1616-1634 °F) Undetermined. Not applicable.
 Eye protection: Protective goggles are recommended, deperation: Wear suitable protective clothing, dependin Physical and chemical properties Physical and chemical properties Information on basic physical and chem General Information Appearance: Form: Color: Odor: Odor threshold: Change in condition Melting point/Melting range: Boiling point/Boiling range: 	ical properties Solid Brass yellow Odorless Not determined. 880-890 °C (1616-1634 °F) Undetermined.



Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

	(Contd. of page 5)
· Solubility in / Miscibility with wat	er at 20 °C (68
°F):	Not soluble. g/l
 Solvent separation test 	
VOC content:	0.00 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity: Not applicable.
- · Chemical stability: Not applicable.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.

• Additional toxicological information:

When used and handled according to specifications, the article does not have any harmful effects to our experience and the information provided to us.

- · Carcinogenic categories
- IARC (International Agency for Research on Cancer)

7439-92-1 lead: 2B 7440-02-0 nickel: 2B

• NTP (National Toxicology Program)

7439-92-1 lead: R 7440-02-0 nickel: R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

(Contd. of page 6)

12 Ecological information

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable to metals.
- · **vPvB:** Not applicable to metals.
- Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Contact manufacturer for recycling information.

14 Transport information

UN-Number		
DOT, ADR, IMDG, IATA	Void	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
DOT, ADR, IMDG, IATA	Void	
Environmental hazards:	Not applicable.	
Special precautions for user:	Not applicable.	
Transport in bulk according to Annex	ll of	
MARPOL73/78 and the IBC Code:	Not applicable.	

(Contd. on page 8)

Page 8/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

(Contd. of page 7)

15 Regulatory information

Safety, health and environmental regulations/le	gislation specific for the substance or mixture
Sara	
Section 355 (extremely hazardous substances):	
None of the ingredients is listed. Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants:	
7439-92-1 lead	
Proposition 65 Chemicals known to cause cancer:	
7439-92-1 lead	
7440-02-0 nickel Chemicals known to cause reproductive toxicit	y for females:
7439-92-1 lead Chemicals known to cause reproductive toxicit	y for males:
7439-92-1 lead Chemicals known to cause developmental toxic	sity:
7439-92-1 lead	
Cancerogenity categories EPA (Environmental Protection Agency):	
7440-50-8 copper: D	
7440-66-6 zinc: D, I, II	
7439-92-1 lead: B2	
TLV (Threshold Limit Value established by ACC	ilH):
7439-92-1 lead: A3	
7440-02-0 nickel: A5	
NIOSH-Ca (National Institute for Occupational S	afety and Health):
7440-02-0 nickel	
Chemical safety assessment: Void.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific article features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Associations & Management Systems

(Contd. on page 9)

US



(Contd. of page 8)

119

Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing date 07/11/2022

Version - No. 11

Reviewed on 07/11/2022

Trade name: Wieland-Z62

· Contact:

Dr. Stefan Priggemeyer

Email: stefan.priggemeyer@wieland.com
** Data compared to the previous version altered.