



 A range of red brass threaded fittings.

Features and Benefits:

- Red brass threaded fittings.
- Available in size 1/4 - 2".
- Our bronze threaded fittings are made to DIN ISO 228 and ISO 7.
- Manufactured to BS EN 1254-4
- Fully corrosion resistant.
- Immune to dezincification.
- Hydraulic working temperatures and pressures:

Size (mm)	Working pressure (bar)	
	-20°C to 110°C	>120 to 225°C
1/4" to 3/4"	25	16
1 to 2	16	10
2 to 4	10	6



3000 Range

<p>Elbow Female x Female Thread</p>  <p>3090 From: 1/4" To: 2"</p>	<p>Reduced Elbow Female x Female Thread</p>  <p>3090 From: 3/4" x 1/2" To: 1" x 3/4"</p>	<p>Elbow Male x Female Thread</p>  <p>3092 From: 1/4" To: 2"</p>	<p>Union Elbow Female x Male Thread</p>  <p>3098 From: 3/8" To: 1"</p>	<p>Obtuse Elbow Male x Female Thread</p>  <p>3121 From: 3/8" To: 1.1/2"</p>
<p>Tee - Equal Female Thread All Ends</p>  <p>3130EQ From: 1/4" To: 2"</p>	<p>Cross - Equal Female All Ends</p>  <p>3180 From: 1/2" To: 3/4"</p>	<p>Reduced Coupler Female x Female Thread</p>  <p>3240 From: 3/8" x 1/4" To: 2" x 1.1/2"</p>	<p>Reduced Bush Male x Female Thread</p>  <p>3241 From: 3/8" x 1/4" To: 3" x 2"</p>	<p>Reduced Hex Nipple Male x Male Thread</p>  <p>3245 From: 1/2" x 3/8" To: 1.1/4" x 1"</p>
<p>Straight Coupler Female x Female Thread</p>  <p>3270 From: 1/4" To: 2.1/2"</p>	<p>Hexagon Nipple Male x Male Thread</p>  <p>3280 From: 1/4" To: 2.1/2"</p>	<p>Beaded Blank Plug Male Thread</p>  <p>3290 From: 1/4" To: 2"</p>	<p>Plain Plug Male Thread</p>  <p>3291 From: 1/4" To: 2.1/2"</p>	<p>Blank Cap Female Thread</p>  <p>3301 From: 1/2" To: 2"</p>
<p>Brass Locknut Female Thread</p>  <p>3310 From: 1/4" To: 2"</p>	<p>Female Straight Union Coupler (Flat Joint)</p>  <p>3330 Size: 1.1/4"</p>	<p>Male x Female Straight Union Connector (flat joint)</p>  <p>3331 From: 1/2" To: 1.1/2"</p>	<p>Female Straight Union Coupler (Coned Joint)</p>  <p>3340 From: 1/4" To: 2"</p>	<p>Male x Female Straight Union Connector (coned joint)</p>  <p>3341 From: 1/4" To: 2"</p>
<p>Extension Piece Female x Male Thread</p>  <p>3526 From: 1/2" x 30mm long To: 1" x 60mm long</p>	<p>Male Thread (Parallel)</p>  <p>3531 Size: 1/2"</p>	<p>Barrel Nipple Male x Male Thread</p>  <p>3533 From: 1/2" To: 1.1/2"</p>		



*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
 Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: sales@ibpgroup.com | Website: www.conexbanninger.com

 an IBP GROUP company

This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries.