

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Länge	Endenausführung
mm	kg/m					mm	
eco SW1®, CuZn21Si3P, CW724R, EN 12164/C69300							
Rundstange, 3.000 mm							
7,0	0,317	●	479207000	R670	+0/-0,036		
8,0	0,415	●	479208000				
9,0	0,525	●	479209000				
10,0	0,648	○	479210000				
11,0	0,784	○	479211000				
12,0	0,933	○	479212000				
13,0	1,095	○	479213000	R600	+0/-0,043	± 50	angefast/angespitzt
14,0	1,270	○	479214000				
15,0	1,458	○	479215000				
16,0	1,659	○	479216000				
17,0	1,873	○	479217000				
18,0	2,099	○	479218000				
19,0	2,339	○	479219000				
20,0	2,592	○	479220000				
22,0	3,136	○	479222000				
23,0	3,428	○	479223000				
24,0	3,732	○	479224000				
25,0	4,050	○	479225000				
27,0	4,724	○	479227000	R500	+0/-0,052	± 100	beidseitig angefast
28,0	5,080	○	479228000				
30,0	5,832	○	479230000				
32,0	6,635	○	479232000				
35,0	7,937	○	479235000				
38,0	9,356	○	479238000				
40,0	10,367	○	479240000				
42,0	11,430	○	479242000				
45,0	13,114	○	479245000				
48,0	14,929	○	479248000				
50,0	16,199	○	479250000				

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Länge	Enden- ausführung
mm	kg/m					mm	
ecobrass SW4®, CuZn21Si3P, CW724R, EN 12164/C69305							
Rundstange, 3.000 mm							
10,0	0,649	●	479610000	R500	+0/-0,036	± 50	angefast/angespitzt
11,0	0,785	●	479611000				
12,0	0,934	●	479612000				
13,0	1,096	○	479613000				
14,0	1,272	○	479614000				
15,0	1,460	○	479615000				
16,0	1,661	○	479616000				
17,0	1,875	○	479617000				
18,0	2,102	○	479618000				
19,0	2,342	○	479619000				
20,0	2,595	○	479620000				
21,0	2,861	○	479621000				
22,0	3,136	○	479622000				
23,0	3,432	○	479623000				
24,0	3,737	○	479624000				
25,0	4,055	○	479625000				
26,0	4,385	○	479626000				
27,0	4,729	○	479627000				
28,0	5,086	○	479628000				
30,0	5,832	○	479630000				
32,0	6,643	○	479632000				
33,0	7,065	○	479633000	+0/-0,16	± 100	beidseitig angefast	
34,0	7,490	○	479634000				
35,0	7,947	○	479635000				
38,0	9,356	○	479638000				
40,0	10,367	○	479640000				
45,0	13,121	○	479645000				
48,0	14,929	○	479648000				
50,0	16,199	○	479650000				

Standardverpackung:

- = in Holzkisten von ca. 500 kg,
≤ 5,5 mm in Kleinbunden von 25 kg
- = in Bunden von ca. 500 kg,
alternativ in Bunden von ca. 1.000 kg möglich

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranzklasse	Länge	Endenausführung
mm	kg/m					mm	
eco SZ3®, CuZn40SiP							
Rundstange, 3.000 mm							
3,0	0,060	x	444303000	W-R520	h9	± 50	angefast/angespitzt
4,0	0,106	x	444304000				
5,0	0,166	x	444305000				
6,0	0,232	●	444306000				
7,0	0,316	●	444307000				
8,0	0,413	●	444308000				
9,0	0,522	●	444309000				
10,0	0,645	o	444310000				
11,0	0,780	o	444311000				
12,0	0,929	o	444312000				
13,0	1,090	o	444313000				
14,0	1,264	o	444314000				
15,0	1,451	o	444315000				
16,0	1,651	o	444316000				
17,0	1,864	o	444317000	W-R460	h11	± 100	beidseitig angefast
18,0	2,089	o	444318000				
19,0	2,328	o	444319000				
20,0	2,579	o	444320000				
22,0	3,121	o	444322000				
24,0	3,714	o	444324000				
25,0	4,030	o	444325000				
26,0	4,359	o	444326000				
27,0	4,701	o	444327000				
28,0	5,055	o	444328000				
30,0	5,803	o	444330000				
32,0	6,603	o	444332000				
35,0	7,899	o	444335000				
40,0	10,317	o	444340000				
45,0	13,057	o	444345000				
50,0	16,120	o	444350000				
60,0	23,213	o	444360000				

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranzklasse	Länge	Endenausführung
mm	kg/m					mm	
eco SZ4®, CuZn42, CW510L, EN12164							
Rundstange, 3.000 mm							
4,0	0,103	x	444404000	R500	h9	± 50	angefast/angespitzt
5,0	0,161	x	444405000				
6,0	0,232	●	444406000				
7,0	0,318	●	444407000				
8,0	0,412	●	444408000				
9,0	0,525	●	444409000				
10,0	0,644	o	444410000				
12,0	0,927	o	444412000				
14,0	1,262	o	444414000				
16,0	1,661	o	444416000				
18,0	2,102	o	444418000				
20,0	2,576	o	444420000				
25,0	4,055	o	444425000				
30,0	5,796	o	444430000				
35,0	7,947	o	444435000	R430	h11	± 100	beidseitig angefast
40,0	10,304	o	444440000				
45,0	13,042	o	444445000				
50,0	16,120	o	444450000				
50,0	16,120	o	444450000				
60,0	23,213	o	444460000				

Standardverpackung:

x = in Holzkisten von ca. 250 kg

● = in Holzkisten von ca. 500 kg,

≤ 5,5 mm in Kleinbunden von 25 kg

o = in Bunden von ca. 500 kg,

alternativ in Bunden von ca. 1.000 kg möglich