

Dimension	Weight	Packaging	Material No.	Condition	Tolerance	Length	End Finish
mm	kg/m					mm	
eco SW1®, CuZn21Si3P, CW724R, EN 12164/C69300							
Round rod, 3,000 mm							
7.0	0.317	●	479207000	R670	+0/-0.036	± 50	chamfered/pointed
8.0	0.415	●	479208000				
9.0	0.525	●	479209000				
10.0	0.648	○	479210000				
11.0	0.784	○	479211000				
12.0	0.933	○	479212000				
13.0	1.095	○	479213000	R600	+0/-0.043	± 50	chamfered/pointed
14.0	1.270	○	479214000				
15.0	1.458	○	479215000				
16.0	1.659	○	479216000				
17.0	1.873	○	479217000				
18.0	2.099	○	479218000				
19.0	2.339	○	479219000				
20.0	2.592	○	479220000				
22.0	3.136	○	479222000				
23.0	3.428	○	479223000				
24.0	3.732	○	479224000	R500	+0/-0.052	± 100	both ends chamfered
25.0	4.050	○	479225000				
27.0	4.724	○	479227000				
28.0	5.080	○	479228000				
30.0	5.832	○	479230000				
32.0	6.635	○	479232000				
35.0	7.937	○	479235000				
38.0	9.356	○	479238000				
40.0	10.367	○	479240000				
42.0	11.430	○	479242000				
45.0	13.114	○	479245000	R500	+0/-0.16	± 100	both ends chamfered
48.0	14.929	○	479248000				
50.0	16.199	○	479250000				

Dimension	Weight	Packaging	Material No.	Condition	Tolerance	Length	End Finish
mm	kg/m					mm	
ecobrass SW4®, CuZn21Si3P, CW724R, EN 12164/C69305							
Round rod, 3,000 mm							
10.0	0.649	●	479610000	R500	+0/-0.036	± 50	chamfered/pointed
11.0	0.785	●	479611000				
12.0	0.934	●	479612000				
13.0	1.096	○	479613000				
14.0	1.272	○	479614000				
15.0	1.460	○	479615000				
16.0	1.661	○	479616000				
17.0	1.875	○	479617000				
18.0	2.102	○	479618000				
19.0	2.342	○	479619000				
20.0	2.595	○	479620000	R500	+0/-0.043	± 50	chamfered/pointed
21.0	2.861	○	479621000				
22.0	3.136	○	479622000				
23.0	3.432	○	479623000				
24.0	3.737	○	479624000				
25.0	4.055	○	479625000				
26.0	4.385	○	479626000				
27.0	4.729	○	479627000				
28.0	5.086	○	479628000				
30.0	5.832	○	479630000				
32.0	6.643	○	479632000	R500	+0/-0.052	± 100	both ends chamfered
33.0	7.065	○	479633000				
34.0	7.490	○	479634000				
35.0	7.947	○	479635000				
38.0	9.356	○	479638000				
40.0	10.367	○	479640000				
45.0	13.121	○	479645000				
48.0	14.929	○	479648000				
50.0	16.199	○	479650000				

Standard Packaging:

- = wooden boxes of approx. 500 kg,
≤ 5,5 mm in small bundles of 25 kg
- = bundles of approx. 500 kg,
alternatively bundles of approx. 1,000 kg are possible

Dimension	Weight	Packaging	Material No.	Condition	Tolerance (class)	Length	End Finish
mm	kg/m					mm	
eco SZ3®, CuZn40SiP Round rod, 3,000 mm							
3.0	0.060	x	444303000	W-R520	h9	± 50	chamfered/pointed
4.0	0.106	x	444304000				
5.0	0.166	x	444305000				
6.0	0.232	●	444306000				
7.0	0.316	●	444307000				
8.0	0.413	●	444308000				
9.0	0.522	●	444309000				
10.0	0.645	o	444310000				
11.0	0.780	o	444311000				
12.0	0.929	o	444312000				
13.0	1.090	o	444313000				
14.0	1.264	o	444314000				
15.0	1.451	o	444315000				
16.0	1.651	o	444316000				
17.0	1.864	o	444317000	W-R460	h11	± 100	both ends chamfered
18.0	2.089	o	444318000				
19.0	2.328	o	444319000				
20.0	2.579	o	444320000				
22.0	3.121	o	444322000				
24.0	3.714	o	444324000				
25.0	4.030	o	444325000				
26.0	4.359	o	444326000				
27.0	4.701	o	444327000				
28.0	5.055	o	444328000				
30.0	5.803	o	444330000				
32.0	6.603	o	444332000				
35.0	7.899	o	444335000				
40.0	10.317	o	444340000				
45.0	13.057	o	444345000				
50.0	16.120	o	444350000				
60.0	23.213	o	444360000				

Dimension	Weight	Packaging	Material No.	Condition	Tolerance (class)	Length	End Finish
mm	kg/m					mm	
eco SZ4®, CuZn42, CW510L, EN12164 Round rod, 3,000 mm							
4.0	0.103	x	444404000	R500	h9	± 50	chamfered/pointed
5.0	0.161	x	444405000				
6.0	0.232	●	444406000				
7.0	0.318	●	444407000				
8.0	0.412	●	444408000				
9.0	0.525	●	444409000				
10.0	0.644	o	444410000				
12.0	0.927	o	444412000				
14.0	1.262	o	444414000				
16.0	1.661	o	444416000				
18.0	2.102	o	444418000				
20.0	2.576	o	444420000				
25.0	4.055	o	444425000				
30.0	5.796	o	444430000				
35.0	7.947	o	444435000	R430	h11	± 100	both ends chamfered
40.0	10.304	o	444440000				
45.0	13.042	o	444445000				
50.0	16.120	o	444450000				
50.0	16.120	o	444450000				
60.0	23.213	o	444460000				

Standard Packaging:

x = wooden boxes of approx. 250 kg

● = wooden boxes of approx. 500 kg,

≤ 5,5 mm in small bundles of 25 kg

o = bundles of approx. 500 kg,

alternatively bundles of approx. 1,000 kg are possible