





















>B< Press Gas fitting is an innovative press system which provides a secure fitting for gas applications.

Features and Benefits:

- Available in copper and red brass fittings.
 - Compatible with various press tools and jaws.*
 - >B< Press Gas is quick and simple to install, saving time and money.
 - Flame free installation for ensuring on site safety.
 - >B< Profile 3 point press ensures a leak free, secure and permanent joint.
 - Available in 15mm to 54mm.
 - Suitable for use with hard, half-hard and soft copper tubes to EN 1057.
 - Manufactured and designed to BS 8537 copper tube press fittings.
 - Designed with a mechanical hexagonal press form which indicates fittings has been secured ensuring no joint rotation.
 - >B< Press Gas has a high quality O-Ring material that forms a secure leak free joint when pressed.
 - Leading edge design ensures the chances of damaging the O-Rings are reduced during installation.
- *Please see compatibility list on website for more details



>B< Press Gas range with Pressing Indicator

<p>Straight Coupler</p>  <p>PG1 (P5270) From: 15mm To: 54mm</p>	<p>Slip Coupler</p>  <p>PG1S (P4275) From: 15mm To: 54mm</p>	<p>Female Straight Connector</p>  <p>PG2 (P4270G) From: 15 x 1/2" To: 54 x 2"</p>	<p>Male Straight Connector</p>  <p>PG3 (P4243G) From: 15 x 1/2" To: 54 x 2"</p>	<p>Fitting Reducer</p>  <p>PG6 (P5243) FFrom: 22 x 15mm To: 54 x 42mm</p>
<p>90° Elbow</p>  <p>PG12 (PC5002) From: 15mm To: 54mm</p>	<p>90° Street Elbow</p>  <p>PG12S (P4001G) From: 15mm To: 54mm</p>	<p>90° Bend with Male Thread</p>  <p>PG13 (P4001G) From: 15 x 1/2" To: 54 x 2"</p>	<p>90° Elbow with Female Thread</p>  <p>PG14 (P4090G) From: 15 x 1/2" To: 54 x 2"</p>	<p>45° Obtuse Elbow</p>  <p>PG21 (P5041) From: 15mm To: 54mm</p>
<p>45° Obtuse Street Elbow</p>  <p>PG21S (P5040) From: 15mm To: 54mm</p>	<p>Tee</p>  <p>PG24 (P5130) From: 15mm To: 54mm</p>	<p>Tee Reduced Branch</p>  <p>PG25 (P5130) From: 22 x 15 x 22mm To: 54 x 42 x 54mm</p>	<p>Tee Reduced End</p>  <p>PG26 (P5130) From: 22 x 15 x 22mm To: 28 x 22 x 28mm</p>	<p>Tee Reduced End & Branch</p>  <p>PG27 (P5130) From: 22 x 15 x 15mm To: 54 x 42 x 42mm</p>
<p>Threaded Tee Reduced End & Branch</p>  <p>PG30 (P4130) From: 15 x 1/2 x 15mm To: 54 x 1/2 x 42mm</p>	<p>Stop End</p>  <p>PG61 (P5301) From: 15mm To: 54mm</p>			

- Specially designed HNBR O-Ring making >B< Press Gas suitable for natural, LPG gas and compressed air applications.
- Designed for maximum operating pressure up to 5 bar.
- Designed for temperature between -20°C to 70°C.
- Approved by WRAS, KIWA, DVGW, CERTIGAS and ARBG/KVBG.
- Designed and manufactured to BS.8537:2010.



*Conex | Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
Tel: +44 (0)121 521 2921 | Fax: +44 (0)121 557 0185 | Email: international@ibpgroup.com | Website: www.conexbanninger.com

This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries.

an IBP GROUP company