

Cutting steel PX round bars

updated on: february 2019

| | | | |
|-------------|--------------------------------|--------------|-----------------------------------|
| material | 11SMnPb37 / WNr. 1.0737 | availability | ● Stock Wieland Metalix AG |
| standard | EN 10277 / EN 10278 | | CH-4512 Bellach |
| execution | pulled, tolerance h9 | | |
| length (mm) | 3000 ± 50 | | |

| dimension | mass | availability |
|-----------|-------|--------------|
| [mm] | kg/m | |
| 1.5 | 0.014 | ● |
| 2 | 0.025 | ● |
| 2.2 | 0.030 | ● |
| 2.4 | 0.036 | ● |
| 2.5 | 0.039 | ● |
| 2.8 | 0.048 | ● |
| 3 | 0.055 | ● |
| 3.2 | 0.063 | ● |
| 3.5 | 0.076 | ● |
| 4 | 0.099 | ● |
| 4.5 | 0.125 | ● |
| 5 | 0.154 | ● |
| 5.5 | 0.185 | ● |
| 6 | 0.222 | ● |
| 6.5 | 0.260 | ● |
| 7 | 0.302 | ● |
| 7.5 | 0.344 | ● |
| 8 | 0.395 | ● |
| 8.5 | 0.445 | ● |
| 9 | 0.499 | ● |
| 9.5 | 0.556 | ● |
| 10 | 0.616 | ● |
| 11 | 0.746 | ● |
| 11.5 | 0.815 | ● |
| 12 | 0.888 | ● |
| 13 | 1.042 | ● |
| 13.5 | 1.124 | ● |
| 14 | 1.208 | ● |

| dimension | mass | availability |
|-----------|--------|--------------|
| [mm] | kg/m | |
| 15 | 1.387 | ● |
| 16 | 1.578 | ● |
| 16.5 | 1.678 | ● |
| 17 | 1.782 | ● |
| 18 | 1.998 | ● |
| 19 | 2.226 | ● |
| 20 | 2.466 | ● |
| 21 | 2.719 | ● |
| 22 | 2.884 | ● |
| 23 | 3.262 | ● |
| 24 | 3.551 | ● |
| 25 | 3.853 | ● |
| 26 | 4.168 | ● |
| 27 | 4.495 | ● |
| 28 | 4.834 | ● |
| 29 | 5.185 | ● |
| 30 | 5.549 | ● |
| 31 | 5.925 | ● |
| 32 | 6.313 | ● |
| 33 | 6.714 | ● |
| 34 | 7.127 | ● |
| 35 | 7.553 | ● |
| 36 | 7.990 | ● |
| 37 | 8.440 | ● |
| 38 | 8.903 | ● |
| 40 | 9.855 | ● |
| 41 | 10.360 | ● |
| 42 | 10.880 | ● |

| dimension | mass | availability |
|-----------|--------|--------------|
| [mm] | kg/m | |
| 43 | 11.400 | ● |
| 45 | 12.480 | ● |
| 50 | 15.410 | ● |
| 60 | 22.200 | ● |

Further dimensions and alloys on request

This datasheet only informs and is not subject to change management. Apart from intent or gross negligence, we assume no liability for its accuracy. Product features are considered unsecured.